



Packaging Supplies and Equipment

Sales and Service of Nordson, Slautterback and ITW Dynatec Hot Melt Systems
317-841-1126 INFO@HOTMELTUNITS.COM



Honeybee Hot Melt Unit

The Honeybee all-electric manual hotmelt applicator system is an excellent choice for reliable packaging and product assembly. It provides a fast and economical alternative to traditional methods such as tape, cold glue, and metal fasteners.



- **Simple all-electric design**
- **Lightweight and easy to move**
- **Adjustable temperature and flow rates.**
- **Fan-Cooled 25rpm AC Gear Motor**
- **120V Unit**



Performance:

- Warm-up Time: 30 minutes
- Melt Rate: 10lb/hr
- Viscosity: Maximum 5,500cps
- Operating Temperature: 100-375F
- Tank Overtemp Switch

Specifications:

- Length: 15 in
- Width : 12 in
- Height : 15 in
- Weight : 30 lbs
- Volume: 7lbs



Versus



The all-new tabletop Honeybee Hotmelt Unit enables the use of bulk adhesive instead of sticks, allowing for a wider variety of hot melt options from virtually any supplier. Using bulk glue is significantly more cost-effective, often being half the price of stick glue.

Another major advantage over stick guns is the ability to apply long glue beads without waiting for the gun to melt more glue. The Honeybee can lay down a continuous 1/8" bead for over 3,500 feet.

This all-electric 120VAC unit requires no air and is ready to operate after just 30 minutes. Startup and shutdown are as simple as flipping a switch.